



SHENZHEN OTTIMA TECHNOLOGY CO., LTD.

Add: Floor 3, Building 8, Lihao Industrial Park, 78 Ainan Road, Baolong Street, Longgang District, Shenzhen, Guangdong, China.

Tel: 0086-755-89257015 Fax: 0086-755-89257085

Web: <https://szottima.en.alibaba.com> / <https://www.ottima-tech.com>

Triac ELV MLV Dimmable Transformer 60W

Features



**SELV
Class 2
Class P
TYPE HL**

Dimming function:	Electronic Transformer Triac/ ELV/ MLV dimming
Dimming range:	0-100%
Certificates:	UL listed, Class 2, Class P, Type HL, SELV, RoHS
Location of application:	Dry , damp and Wet locations
Input:	120VAC
THD:	THD<20%@120V Max. load
Output type:	Constant voltage
Small size:	126.4x80x40.4 mm / 4.97x3.15x1.59 inch(L*W*H)
Loading:	Super low loading request, works perfect at 20-100% load
Protections:	Short circuit / over load
Compatibility:	Compatible with popular dimmers in the market, Lutron-CL, Diva series and so on.
Application:	• LED strip/ LED tape/ LED module • Residential Lighting • Commercial Lighting
Warranty:	5 years warranty

Specification

Model Number	OTM-TD60-JA12	OTM-TD60-JA24
OUTPUT		
Rated Power	60W	60W
Rated Voltage	12V	24V
Rated Current	5.0A	2.5A
Voltage Tolerance	±1V	±1.5V
INPUT		
Voltage Range	120V	
Frequency Range	47-63Hz	
Power Factor(typ.)	0.94@120VAC	
Total Harmonic Distortion	THD< 20%(@100% load)	
Efficiency (Typ.)	88%@120VAC	
AC Current (Typ.)	0.93A	
Leakage Current	<0.5mA/ 120VAC	
PROTECTION		
Short Circuit	Hiccup mode, recovers automatically after fault condition is removed.	
Over Load	Hiccup mode, recovers automatically after fault condition is removed.	
ENVIRONMENT		
Working Temp.	Tc =-40 ~ +60 (Please refer to“OUTPUTLOAD vs TEMPERATURE”section)	



SHENZHEN OTTIMA TECHNOLOGY CO., LTD.

Add: Floor 3, Building 8, Lihao Industrial Park, 78 Ainan Road, Baolong Street, Longgang District, Shenzhen, Guangdong, China.


Tel: 0086-755-89257015 Fax: 0086-755-89257085

Web: <https://szottima.en.alibaba.com> / <https://www.ottima-tech.com>

Triac ELV MLV Dimmable Transformer 60W

Working humidity	20 ~ 95% RH non-condensing
Storage temp., Humidity	-40 ~ +90, 10 ~ 95% RH
Temp .coefficient	±0.03%/°C (0~50°C)
Vibration	10~500Hz, 5G 10min./1 cycle, period for 60min. each along X,Y,Z axes
SAFETY & EMC	
Safety standards	UL8750, Class 2
Withstand voltage	I/P-O/P: 1.88KVAC
OTHERS	
Weight	0.175/kg
Dimension	See Mechanical Specification
Packing	36*24*19 cm (20PCS/CTN)

Mechanical Specification





SHENZHEN OTTIMA TECHNOLOGY CO., LTD.



Add: Floor 3, Building 8, Lihao Industrial Park, 78 Ainan Road, Baolong Street, Longgang District, Shenzhen, Guangdong, China.

Tel: 0086-755-89257015 Fax: 0086-755-89257085


Web: <https://szottima.en.alibaba.com> / <https://www.ottima-tech.com>

Triac ELV MLV Dimmable Transformer 60W

Wiring Diagram



Load vs Ambient Temperature



❖ To extend their life, please refer to the Derating Curve and derate according to the temperature.

Warm tips :

1. All Electronic Transformer meet the harmonic emissions requirements of ANSI C82.77-10.